

**HELI**  
LIFTING THE FUTURE

# CBD15-610

## Electric Pedestrian Pallet Truck

### Advantages

- Low noise, low energy consumption. Every day only 2kWh.
- HELI controller, Multiple automatic protection. Small body, suitable for narrow space.
- Sealed batteries free of maintenance. Safe operation and no pollution.
- Stepless speed control system, easy to operate.
- Automatic lifting limit, safety, energy saving.
- Emergency reversing device/Emergency brake switch.

### Options

- Built-in charger.
- Min. fork lowered height 75mm



**Mini**

Free-maintained battery

High performance at good price



TOP1 FORKLIFT MANUFACTURER AND SALER  
IN CHINA FOR CONSECUTIVE 24 YEARS

# HELI CBD15-610

Feature		
Model		CBD15
Configuration No.		610
Loading capacity	kg	1500
Load center	mm	600
Wheel base	mm	1234
Operating type		Walkie
Wheels		
Wheels type		PU
Wheel quantity Driving wheel/Balance wheel/Bearing wheel		1/2/4
Driving wheel size	mm	∅252×67
Bearing wheel size	mm	∅84×70(Double wheels)
Balance wheel size	mm	∅99.5×40
Dimension		
Min.fork lowered height	mm	85
Max.fork lifting height	mm	205
Max.lifting height	mm	120
Overall fork width	mm	540/600/650/685
Inside width between forks	mm	220/280/330/365
Fork length	mm	1150/1200
Fork width	mm	160
Fork thickness	mm	75
Overall length	mm	1630
Overall width	mm	724
Overall height(With handle)	mm	1220
Overall height(Without handle)	mm	685
Min.Turning radius	mm	1400
Min.Aisle width for pallets 800×1200	mm	1817
Min.Aisle width for pallets 1000×1200	mm	1858
Performance		
Travel speed,laden/unladen	km/h	3.5/4
Lift speed,laden/unladen	mm/s	56/60
Lowering speed,laden/unladen	mm/s	57/59
Gradeability,laden/unladen	%	5/7
Electrical configuration		
Drive motor	kW	DC 0.63
Lift motor	kW	DC 0.8
Steering motor	kW	/
Battery voltage / capacity	V/Ah	24/70
Brake		Electromagnetic/Regenerative
Controller		HELI(Options CURTIS)
Weight		
Battery weight	kg	48
Service weight with battery	kg	285

\* Details of specifications and equipment are based on information available at time of printing and may change without notice.



### ANHUI HELI INDUSTRIAL VEHICLE IMP. AND EXP. CO., LTD.

ADD: 668 FANGXING ROAD, HEFEI, ANHUI, CHINA  
TEL: +8655163639068  
FAX: +8655163639966  
Email: heli@helichina.net  
WEBSITE: WWW.HELICHINA.COM / WWW.HELI.CHINA.NET

© 2015 heli copyright

Catalog No.2015.04 HELI Print