

HELI
LIFTING THE FUTURE

CBD18/20-180

1.8-2.0 Ton Electric Pedestrian Pallet Trucks

Advantages

- Mechanical Steering-Economic,comfortable,more reliable.
- AC Driving System-Low noise,quiet,without carbon brush and free maintenance.
- Electric Lifting-Rapid,efficient,electricity limit switch is standard.
- Short Wheelbase-Small turning radius,suitable for narrow space.
- Excellent Design-Easily in and out of the double tray.
- Energy conservation-Save energy,every day only 5kW/h.
- AC Controller-Stepless,strong power,multiple automatic protection.

Options

- 140Ah VRLA Battery+Built-in charger.
- Handle upright walking function.



AC | Short wheelbase

Fork suitable for reversible pallet

**Higher performance at best price
Most popular in Europe & America**



TOP1 FORKLIFT MANUFACTURER AND SALER
IN CHINA FOR CONSECUTIVE 24 YEARS

HELI CBD18/20-180

| Feature | | |
|----------------------------------------------------------|------|------------------------------|
| Model | | CBD18/20 |
| Configuration No. | | 180 |
| Loading capacity | kg | 1800/2000 |
| Load center | mm | 600 |
| Wheel base | mm | 1300 |
| Operating type | | Pedestrian |
| Wheels | | |
| Wheels type | | PU |
| Wheel quantity Driving wheel/Balance wheel/Bearing wheel | | 1/1/4 |
| Driving wheel size | mm | ∅228×75 |
| Bearing wheel size | mm | ∅84×80(Double wheels) |
| Balance wheel size | mm | ∅115×55 |
| Dimension | | |
| Min.fork lowered height | mm | 85 |
| Max.fork lifting height | mm | 195 |
| Max.lifting height | mm | 110 |
| Overall fork width | mm | 550/600/650/685 |
| Inside width between forks | mm | 210/260/310/345 |
| Fork length | mm | 1150/1200 |
| Fork width | mm | 170 |
| Fork thickness | mm | 75 |
| Overall length | mm | 1650 |
| Overall width | mm | 725 |
| Overall height(With handle) | mm | 1380 |
| Overall height(Without handle) | mm | 890 |
| Min.Turning radius | mm | 1450 |
| Min.Aisle width for pallets 800×1200 | mm | 1866 |
| Min.Aisle width for pallets 1000×1200 | mm | 1921 |
| Performance | | |
| Travel speed,laden/unladen | km/h | 3.5/4.0 |
| Lift speed,laden/unladen | mm/s | 20/25 |
| Lowering speed,laden/unladen | mm/s | 40/30 |
| Gradeability,laden/unladen | % | 5/7 |
| Electrical configuration | | |
| Drive motor | kW | AC 0.93 |
| Lift motor | kW | DC 1.2 |
| Steering motor | kW | / |
| Battery voltage / capacity | V/Ah | 24/210 |
| Brake | | Electromagnetic/Regenerative |
| Controller | | CURTIS |
| Weight | | |
| Battery weight | kg | 202 |
| Service weight with battery | kg | 552 |

* Details of specifications and equipment are based on information available at time of printing and may change without notice.



ANHUI HELI INDUSTRIAL VEHICLE IMP. AND EXP. CO., LTD.

ADD: 668 FANGXING ROAD, HEFEI, ANHUI, CHINA
TEL: +8655163639068
FAX: +8655163639966
Email: heli@helichina.net
WEBSITE: WWW.HELICHINA.COM / WWW.HELICHINA.NET

© 2015 heli copyright

Catalog No.2015.04 HELI Print